

World Watch Flex

Network Camera

Wireless colour video network camera with Internet monitoring and swivel/inclination control

- Keep a watch on your home or business premises from anywhere in the world
- Keep a watch on the children's room, pool*, garden*, backyard*, office, warehouse hall or any other area that might require surveillance
- Swivel and inclination arrangement that can be controlled remotely from a laptop or computer from anywhere in the world.
- 1/4" CMOS video sensor
- Audio and video monitoring
- Can be mounted on the wall, ceiling or desktop
- Wireless transmission between network camera and access point (IEEE802.11b/g) or wired Ethernet
- UpnP Installation (Universal Plug n Play)
- SSID Filtering and power output 64/128 bit encryption to support the safety of the wireless network from illegal switching
- Up to 16 network cameras can be monitored with the software delivered
- The delivered software has a motion detection component for triggering remote monitoring recording on the PC
- Comes with an AC adapter for operating the network camera

*camera not weatherproof

This versatile system allows you to monitor your home or business premises remotely using your broadband Internet connection. The network camera is provided with a unique IP address which can then be accessed from anywhere in the world using a PC and a broadband connection. The network camera has a pan/tilt facility which can be operated from

the remote location enabling selective coverage of required areas for monitoring.

The supplied PC software can monitor up to 16 network cameras simultaneously and has a motion detection facility which can be used to trigger remote recording on the PC when movement is detected.

	Network camera
Image Sensor	1/4" CMOS
Viewing angle	51°(horizontal), 38.9° (vertical)
Minimum illumination	1 Lux
Pan/Tilt angle	±65°/-60° +10°
Max Pan/Tilt speed	50°/second
Focal length	f=3.7mm
Aperture	F2.0mm
Network	
Image compression	M-PEG4
Image resolution	640 x 480 (VGA), 320 x 240 (QVGA, default), 160 x 120 (QQVGA)
Max frame rate	30 fps (320 x 240), 15 fps (640 x 480)
Connection	IEEE802.11b/g or wired Ethernet (10base-T or 100base-TX)
General	
Operating temperature	-10°C to +50°C
Operating humidity	20% to 80% RH (non condensing)
Power supply	DC 5V 7.5W
Dimensions (WxDxH)	110 x 110 x 110 mm (main body)
Weight	334g (main body)
PC System requirements	
Operating system	Windows 2000/XP
Processor	Intel Pentium III, 1GHz or higher (recommended Pentium IV, 2GHz or higher)
RAM	256MB RAM minimum
Web browser	Microsoft Internet Explorer Version 5.5 or later

All trademarks are acknowledged

We reserve the right to change specifications and design in order to improve the Product without prior notice.
Manufactured in China for and according to the Quality Standards of ENOX WORLD Prime Consumer Electronics Supply GmbH, Germany

enox.
enjoy life



Stay close to your family ...



... by watching them from afar!



Property Watch



Office Watch



enox.

The German
High Tech Brand

electronic
security
for a better Life