





Wireless N 300Mbps USB Adapter

The WL0086A Wireless N 300Mbps USB Adapter is designed for SOHO users. It allows users to enjoy Wireless network and easy wireless security connection. It has an extra foundation which is designed to make Wireless USB Adapter get better signal when it is plugging into the foundation and can be easily move around.

Features

- Complies with IEEE 802.11b/g/n standards
- High transfer data rate up to 300Mbps
- Supports 64/128-bit WEP, WPA, and WPA2
- With WPS button
- Supports USB 2.0/1.1 interface
- Supports Windows 2000/XP/Vista/7, Linux 2.4/2.6, Mac OS up to 10.7

Package Contents:

- 1 x Wireless N USB Adapter
- 1 x Quick Installation Guide
- 1 x CD (Driver + Manual)

Packaging Information:

- Packing Dimension: 166x101x20 mm
- Packing Weight: 0.05kg
- Carton Dimension: 438x335x370 mm
- Carton Q'ty: 200pcsCarton Weight: 11.9kgs













Wireless N 300Mbps USB Adapter

Specification:

Main Chipset	Ralink RT5372
Host interface	USB 2.0/1.1 Type A
LED	Link/ Activity
Antennas	2 built-in onboard PCB antennas
Operation Frequency	2412~2484MHz
Typical Transmit Power	802.11b (CCK) 11Mbps: 19+/-1dBm
	802.11g (OFDM) 54Mbps: 15+/-1dBm
	802.11n (HT20@MCS7), 14+/-1dBm
	802.11n (HT40@MCS7),14+/-1dBm
Receive Sensitivity	802.11b: -88+/-1dBm, 802.11g: -73+/-1dBm,
	802.11n (HT20), -71+/-1dBm, 802.11n (HT40), -68+/-1dBm
Operation System	Windows 2000/XP/Vista/7; Linux 2.6.X; Mac OS X
Security	WEP 64/128bit , WPA, WPA2, 802.1x, and 802.11i
	Cisco CCS V1.0, 2.0 and V3.0 Compliant
Voltage Range/Current	DC 5.0V ± 5% / <350mA @802.11g
Operating Temp.	-10°C - 60°C
Storage Temperature	-20°C - 70°C
Operating Humidity	RH 95% (Non-Condensing)
Storage Humidity	RH 95% (Non-Condensing)
Dimensions	42*16.8*4.5mm



