

Datasheet

Wireless Speakerphone - OfficeCore M220

M220 speakerphone is an updating version of M2, which includes two M2s in one pack. Based on M2, M220 achieved daisy chain function and increased volume. It could be used both in cascaded or stand-alone. M220 is able to meet conference needs of up to 16 people and greatly expand the effectively meeting space.



● EAN : 0735632209131

Work with:



Certification:



FEATURES

- **4 smart microphone arrays**, 360° coverage, can pick up sounds from all angles within range
- **Ready for meetings with up to 16 people**, providing clear voices and well-rounded sound
- **Unique VoicelA™ call algorithm**, which can effectively suppress noise, eliminate echo, and enhance human voice for HD voices, automatically eliminate environmental noise, such as keyboard sound, air conditioning sound, etc
- **Lightweight UFO shape design**, with travel protection bag, easily enjoy the beauty of technology
- **Compatible with mainstream communication systems**, seamlessly integrate to achieve call control
- **Intuitive plug-and-play connection capability**, which can be used with computer softphones and unified communication systems in just a few seconds of operation
- **Equipped with a Bluetooth adapter** to provide a farther and more stable connection, in addition to support USB, AUX, Bluetooth multiple connection methods



TECHNICAL SPECIFICATIONS

Audio features	Microphone	4 AI Mic Array x2
	Microphone Parameter	100-10KHz, 85dBFS
	Echo Cancellation	eMeet VoiceIA algorithm
	Noise Reduction	eMeet VoiceIA algorithm
	Two-way Talk	√
	Speaker	2
	Speaker Rate power	3W*2
	Speaker output	85dB
	Speaker SN	> 75dB
	Speaker THD+N	< 1%
Connect	Compatible	Windows, macOS, Android, iOS
	Bluetooth	5.0
	Bluetooth Distance	10m
	Bluetooth A2DP	√
	USB	√
	NFC	—
	3.5mm AUX	√
USB Features	Operate System	Windows® 7 (1080p and under only), Windows 8.1, Windows 10 or higher, macOS™10.10 or higher Google™ Chromebook™ Version 29.0.1547.70 or higher, Linux
		2.4 GHz Intel® Core 2 Duo processor or higher 2 GB RAM or more USB 2.0 port
Input/Output Interface	USB Interface	1xUSB 2.0: Type C,
General specification	Input Voltage	5V (USB power supply)
	Current Consumption	1A
	Operating Temperature	-10°C ~ 40°C (14°F ~ 104°F)
	Storage Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
	Power Consumption	MAX 350mA
	Size	125*125*35mm
	MTBF	30000h
	Color	black
Packaging specification	Net weight (g)	564
	Package dimensions (mm)	205*158*51
	Carton size (mm)	458*296*330
	Qty (PC/CTN)	12
	FCL weight (kg)	12.6
	FCL chargeable weight (kg)	13