

Datasheet

All-in-one HD webcam – C980 Pro

The eMeet C980 Pro HD webcam features 2 integrated omni-directional speakers and 4 AI Array microphones with excellent echo & noise cancellation, which eliminates unwanted ambient noise.

Thanks to its user-friendly plug & play design, it can be easily used with your PC, Mac, LCD screen and other devices. Perfect for video calls, live streams, conferences, and meetings.



FEATURES

- **4 smart microphone arrays**, crystal clear audio with echo & noise cancellation
- **Unique VoicelA™ call algorithm**, which can effectively suppress noise, eliminate echo, and enhance human voice
- **Built in speakers**, equipped with 2 omnidirectional speakers
- **Compatible with mainstream communication systems**, seamlessly integrate to achieve call control
- **Lens 90° wide-angle glass lens** combined with automatic light correction function, can shoot bright high-definition images even in low light
- **Plug and play**, connect the USB plug and you are ready to go, it can be used with computer softphone and unified communication system

● EAN: 0735632209162

Work with:



Certification:





TECHNICAL SPECIFICATIONS

Camera features	Sensor	1/2.7", CMOS, Effective Pixel: 2.07M
	Scanning Mode	Progressive
	Lens	Focus: f=2.88mm, FOV: 90°
	Focus	Fixed focus
	Shutter	1/30s ~ 1/10000s
	Camera bracket	bracket with damper
Audio features	Microphone	4 Microphone Array
	Microphone Parameter	100-10KHz, 26dBFS
	Speaker Number	2
	Speaker Rate power	1W*2
	Speaker SN	> 75dB
	Speaker THD+N	< 1%
USB features	Operate System	Windows® 7 (1080p and under only), Windows 8.1, Windows 10 or higher macOS 10.10 or higher Google Chromebook Version 29.0.1547.70 or higher Linux 2.4 GHz Intel® Core 2 Duo processor or higher 2 GB RAM or more USB 2.0 port
	Color System / Compression	YUY2 / MJPEG
	Video Format	1080p@896p@30fps/25fps, 800x600p@30fps/25fps, 640x480p@30fps/25fps, 640x360p@30fps/25fps
	USB Video Communication Protocol	UVC 1.0 ~ UVC 1.5
I/O	USB Interface	1xUSB 2.0: Type A,
General specification	Input Voltage	5V (USB power supply)
	Current Consumption	500mA
	Operating Temperature	-10°C ~ 40°C (14°F ~ 104°F)
	Storage Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
	Power Consumption	MAX 500mAh
	Size	158*60*70mm
Packaging specification	Net weight (g)	244
	Package dimensions (mm)	173*83*74
	Carton size (mm)	360*260*380
	Qty (PC/CTN)	30
	FCL weight (kg)	11.8
	FCL chargeable weight (kg)	12