

Datasheet

HD webcam - Nova

The eMeet Nova HD webcam has 2 integrated AI Array microphones with excellent echo & noise cancellation, which eliminates unwanted ambient noise.

Thanks to its user-friendly plug & play design, it can be easily used with your PC, Mac, LCD screen and more. Perfect for video calls, live streams, conferences, and meetings.



EAN: 0735632209179

Work with:



Certification:



FEATURES

- 2 smart microphone arrays, crystal clear audio with echo & noise cancellation
- Unique VoicelA ™ call algorithm, which can effectively suppress noise, eliminate echo, and enhance human voice
- Autofocus and compatible with Tripod
- Compatible with mainstream communication systems, seamlessly integrate to achieve call control
- Lens 75 ° wide-angle glass lens combined with automatic light correction function, can shoot bright high-definition images even in low light
- Plug and play, connect the USB plug and you are ready to go, it can be used with computer softphone and unified communication system



TECHNICAL SPECIFICATIONS

Г		T
Camera features	Sensor	1/2.7", CMOS, Effective Pixel: 2.07M
	Scanning Mode	Progressive
	Lens	Focus: f=3.2mm, FOV: 75°
	Focus	Auto focus
	Shutter	1/30s ~ 1/10000s
	Camera bracket	bracket with damper
Audio features USB features	Digital Noise Reduction	2D,3D digital noise reduction
	Microphone	2 Smart Al Array Microphones
	Microphone Parameter	100-10KHz, -33dB
	Speaker Number	additional procurement
	Speaker Rate power	-
	Speaker SN	-
	Operate System	Windows® 7 (1080p and under only), Windows 8.1, Windows 10 or higher macOS 10.10 or higher Google Chromebook Version 29.0.1547.70 or higher Linux 2.4 GHz Intel® Core 2 Duo processor or higher 2 GB RAM or more USB 2.0 port
	Color System / Compression	YUY2 / MJPEG
	Video Format	1080p@896p@30fps/25fps, 800x600p@30fps/25fps, 640x480p@30fps/25fps, 640x360p@30fps/25fps
	USB Video Communication Protocol	UVC 1.0 ~ UVC 1.5
I/O	USB Interface	1xUSB 2.0: Type A,
General specification	Input Voltage	5V (USB power supply)
	Current Consumption	500mA
	Operating Temperature	-10°C ~ 40°C (14°F ~ 104°F)
	Storage Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
	Power Consumption	MAX 500mAh
	Size	100*65*56mm
	Net weight(g)	144
Packaging specification	Package dimensions (mm)	127.5*82*69.5
	Carton size (mm)	387*332*285
	Qty (PC/CTN)	48
	FCL weight (kg)	12.4