

Dual Band Repeater 1200P

Boost your Wi-Fi network!



Do you have trouble getting solid Wi-Fi signals in some parts of your home?

STRONG's Dual Band Repeater 1200P is the perfect solution to extend the coverage of your 802.11ac modem or router in just minutes. At a maximum speed of 1200 Mbit/s, the Dual Band Repeater 1200P is one of the most powerful wall plug dual band 802.11ac Repeaters.

No power outlet goes to waste because the Universal Repeater 1200P is equipped with an extra power socket.

Repeater 1200P is equipped with 1 Gigabit Ethernet port to connect any wired network devices in a fast and convenient way.

The system of 3 optimized internal antennas combined with 802.11ac advanced features will boost a wide and reliable Wi-Fi coverage throughout your home.

The Dual Band Repeater 1200P can also be configured as an outstanding 802.11ac dual band Access Point to immediately improve the Wi-Fi of your existing single band modem without exchanging it by a new one.

Wi-Fi performance



- 802.11ac Wi-Fi standard
- Speed up to 1200 Mbit/s
- Dual Band concurrent Repeater
- Supports 802.11ac/n/b/g/a standards
- 300 Mbit/s @ 2.4 GHz + 867 Mbit/s @ 5 GHz
- Works with any standard modem or router

Coverage & Reliability



- Universal Repeater/Access Point operational modes
- PAIR (WPS) button for an easy setup

Security



- WPA/WPA2 for the highest level of Wi-Fi security
- PAIR button for a maximum network security

Connections



- 1x Gigabit Ethernet port to connect any computer, set-top-box, Smart TV, game console, ... or to connect to modem in an Access Point configuration
- Extra Power Socket

Dual Band Repeater 1200P

Wi-Fi

| | |
|--------------------|---|
| Frequency | 2.4 GHz and 5 GHz concurrent |
| Standards | IEEE 802.11ac/n/a 5GHz IEEE 802.11n/g/b 2.4GHz |
| Signal Rate | 5 GHz: Up to 867 Mbit/s 2.4 GHz: Up to 300 Mbit/s |
| Security | WEP, WPA-Personal, WPA2-Personal, WPA-Personal/WPA2-Personal mixed mode |
| Transmit Power | Europe: <20 dBm (2.4 GHz), <23 dBm (5 GHz) |
| Supported Channels | 5 GHz: 36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112 2.4 GHz: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13 |
| Features | Enable/Disable, Transmit Beamforming, Client Isolation |

Hardware

| | |
|----------------|---|
| Ethernet Ports | 1x 10/100/1000 Mbit/s port (Auto MDI/MDIX) |
| Buttons | PAIR/Reset |
| LEDs | Power, PAIR, 2.4 GHz, 5 GHz, LAN |
| Power | Internal, 100-240 V, 50/60 Hz |
| Standards | IEEE 802.11ac/n/g/b/a, IEEE 802.3, IEEE 802.3u |

Software

| | |
|-----------------------|---|
| Configuration Wizards | Repeater, Access Point |
| DHCP | Auto, Server, Client |
| Management | Web User Interface, Time Settings, Configuration Backup/Restore, Firmware Upgrade |
| Internet Protocol | IPv4 |

Other specifications

| | |
|------------------------|---|
| Certification | CE |
| Package contents | Dual Band Repeater 1200P Ethernet Cable Installation instructions Warranty Card |
| System requirements | Windows 7, 8, 8.1, 10, Mac OS X, Linux, Internet Browser |
| Environment | Operating temperature: 0° C ~ +40° C Storage temperature: -40° C ~ +70° C Operating humidity: 10%~90% non-condensing Storage humidity: 5%~90% non-condensing |
| Dimensions (W x D x H) | 114 x 57 x 31mm |
| Weight: | 0.11 kg |

EAN REPEATER1200PEU: 9120072371738